



1063 West Washington Ave. • P.O. Box 126 • Cleveland, WI 53015
Website: www.mekco.com • E-Mail: build@mekco.com
Telephone: 920-693-8163 • FAX: 920-693-8444

DIVISION 13

SECTION 13129

FIBERGLASS EQUIPMENT ENCLOSURE

Part 1 - GENERAL

1.01 Section includes:

This section specifies prefabricated fiberglass enclosures.

Part 2 - PRODUCTS

2.01 Fiberglass Enclosures

- A. Enclosure to be constructed of impact resistant fiberglass reinforced plastic.
- B. Enclosure shall be white in color and have a high gloss molded finish.
- C. Enclosure shall have a removable door 56 1/2" wide (min.) x 36" high. The body shall be of molded one piece construction with a lifting eye.
- D. Enclosure can be optionally equipped with two 12" x 12" stainless steel vents located on opposite walls, with insect screens and manual F.R.P. damper.
- E. Enclosure to be sandwich composite insulated, all walls and roof, yielding an overall wall thickness of 1 1/4".
- F. A continuous 3" mounting flange of 1/4" minimum thickness shall be provided along the bottom perimeter.
- G. Enclosure shall be lockable and all hardware shall be of stainless steel construction.
- H. Inside dimension shall be 70"L X 58"W x 60"H nominally.
- I. Door opening shall have a gasketed seal.
- J. Enclosure shall be **MEKCO** Model 655-R7.

Part 3 - EXECUTION

3.01 Installation

Enclosure shall be installed per manufacturer's recommendations and as shown on the drawings.