



1063 West Washington Ave. • P.O. Box 126 • Cleveland, WI 53015  
Website: [www.mekco.com](http://www.mekco.com) \* E-Mail: [build@mekco.com](mailto:build@mekco.com)  
Telephone: 920-693-8163 \* FAX: 920-693-8444

DIVISION 13

SECTION 13129

FIBERGLASS EQUIPMENT ENCLOSURE

Part 1 – GENERAL

1.01 Section includes:

This section specifies prefabricated fiberglass enclosures.

Part 2 – PRODUCTS

2.01 Fiberglass Enclosures

- A. Enclosure to be constructed of impact resistant fiberglass reinforced plastic.
- B. Enclosure shall be white in color and have a high gloss molded finish.
- C. Enclosure shall have a removable door 56 ½" wide (min.) x 36" high. The body shall be of molded one-piece construction with a lifting eye.
- D. Enclosure can be optionally equipped with two 12" x 12" stainless steel vents located on opposite walls, with insect screens and manual F.R.P. damper.
- E. The wall thickness of the enclosure shall be 3/16" minimum.
- F. A continuous 3" mounting flange of ¼" minimum thickness shall be provided along the bottom perimeter.
- G. Enclosure shall be lockable and all hardware shall be of stainless steel construction.
- H. Inside dimension shall be 72" W x 60" L x 61" H nominally.
- I. Door opening shall have a gasketed seal.
- J. Enclosure shall be **MEKCO** Model 655.

Part 3 – EXECUTION

3.01 Installation

Enclosure shall be installed per manufacturer's recommendations and as shown on the drawings.